

USB MIDI Network Box(UR-1)



Instructions

1. Product Introduction

The USB MIDI network box UR-1 (hereinafter referred to as the product) can be used as a gateway for USB MIDI interface devices. It can connect devices with USB MIDI interfaces to computers in the network through the Ethernet RTP-MIDI interface. Computers on the network, such as Windows, MacBook, mobile phones, etc., can communicate with the product; in addition, UR-1 can also be directly controlled by any other Ethernet RTP-MIDI device, such as the main keyboard or DAW controller, without having to use a computer in the network path.

2. Product Parameters

Name	Description
Model	UR-1
Size (LxWxH)	84*50*36mm
Weight	100g
USB MIDI Interface	Standard USB MIDI HOST interface
Ethernet Interface	Standard Ethernet RTP-MIDI interface
Indicator Light	Network communication indicator
Power In Interface	Use DC interface for power supply, supply voltage 5V~9VDC
USB MIDI Compatibility	Compatible with all musical instruments with USB MIDI TO HOST standard interface

3. Product Interface



- ① USB HOST: MIDI device connected to USB To HOST interface.
- ② DC IN 5V~9V: Product power supply interface, using DC5.5*2.1 plug to supply power to the product, supply voltage 5V~9VDC.
- ③ MIDI LAN: Ethernet interface to connect Ethernet devices, such as routers and switches.

4. Product Connection

