


Features

- Aluminum 6063, good heat radiation with long lifespan;
- Support 0~10V, PWM and Resistor dimming solution;
- High lighting efficiency, save energy;
- Long lifespan, ≥ 50000 hours;
- Light source adopts LM-80 certified LED;
- Adopt UL Class P certified power supply;



Parameter

Size	2460mm(8.07ft)X55mm(0.18ft)X36mm(0.12ft)
Beam angle	93°(PDM)
Working voltage	100~277VAC /50~60Hz
PF	≥ 0.9
Input power	47W (5.8W/ft)
CCT	3000K/4000K/6000K (3500K 、 5000K)
CRI	80+/90+
Lumen	3325~3530lm(415~441lm/ft)
Energy efficiency	A
Dimming range	1~100%
Operating temperature	-20°C~+45°C
Storage temperature	-40°C~+60°C
Humidity	40~75% RH
IP grade	IP40
Installation way	Recessed
Package size	2570mm(8.43ft)X110mm(0.36ft)X80mm(0.26ft)
Gross Weight	3.58Kg



Size



Standard color




PDM



UGR<19

Installation accessories



- N Shape clip



R5536-BI





- Rubber sucker



L-DA-A

Test report



Remark:

- Output data is from test result of 4ft PDM linear light fixture;
- Tolerance $\pm 10\%$;