


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:220.19V I:0.2127A P:44.596W PF:0.9524 Freq:49.99Hz Lamp Flux:5071.25x1 lm					
NAME: L8989-NW45		TYPE:L8989-NW45		WEIGHT:	
SPEC.:1228*89*89		DIM.: 1228*89*89		SERIAL No.:1#	
MFR.: BLUEVISION		SUR.:1228*89		Shielding Angle:	

DATA OF LAMP		PHOTOMETRIC DATA				Eff: 113.72 lm/W
MODEL	L8989-NW45	Imax(cd)	1889	S/MH(C0/180)	1.22	
NOMINAL POWER(W)	44.5	LOR(%)	100.0	S/MH(C90/270)	1.29	
RATED VOLTAGE(V)	220	TOTAL FLUX(lm)	5071.3	η UP,DN(C0-180)	0.5,45.2	
NOMINAL FLUX(lm)	5071.25	CIE CLASS	DIRECT	η UP,DN(C180-360)	0.5,53.9	
LAMPS INSIDE	1	η up(%)	0.9	CIBSE SHR NOM	1.25	
TEST VOLTAGE(V)	220	η down(%)	99.1	CIBSE SHR MAX	1.35	

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:l
 Test Date:2019-08-16

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.412
 Humidity:65.0%
 Test Distance:9.650m [K=1.0000]
 Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum, lamp
10	1837	1791	1783	1817	1832	1874	1878	1848	0- 10	176.9	176.9	3.49,3.49
20	1720	1633	1616	1681	1712	1790	1794	1739	10- 20	502.0	678.9	13.4,13.4
30	1540	1420	1396	1483	1527	1630	1633	1562	20- 30	747.9	1427	28.1,28.1
40	1310	1169	1141	1243	1296	1415	1416	1334	30- 40	882.7	2310	45.5,45.5
50	1048	896.7	868.2	976.9	1033	1161	1162	1075	40- 50	895.9	3205	63.2,63.2
60	764.8	609.8	583.6	694.3	749.6	883.5	887.9	795.0	50- 60	793.8	3999	78.9,78.9
70	468.9	320.0	299.1	404.9	455.2	592.9	601.0	504.1	60- 70	594.3	4594	90.6,90.6
80	186.3	76.43	64.92	139.4	176.0	301.7	313.4	220.8	70- 80	333.0	4927	97.1,97.1
90	3.860	2.673	2.588	2.506	2.049	64.21	72.36	21.84	80- 90	96.65	5023	99.1,99.1
100	3.373	4.080	4.004	3.514	3.317	2.516	2.279	2.847	90-100	7.233	5030	99.2,99.2
110	4.970	5.690	5.655	5.108	4.890	3.847	3.594	4.271	100-110	4.197	5035	99.3,99.3
120	6.707	7.440	7.450	6.867	6.557	5.342	5.111	5.870	110-120	5.510	5040	99.4,99.4
130	8.489	9.224	9.220	8.713	8.360	7.069	6.795	7.608	120-130	6.526	5047	99.5,99.5
140	10.22	10.88	10.86	10.51	10.07	8.893	8.541	9.366	130-140	6.999	5054	99.7,99.7
150	11.77	12.38	12.37	12.11	11.64	10.74	10.40	11.11	140-150	6.742	5060	99.8,99.8
160	13.01	13.53	13.73	13.40	12.87	12.33	12.12	12.55	150-160	5.670	5066	99.9,99.9
170	13.91	14.31	14.76	14.25	13.90	13.69	13.77	13.81	160-170	3.816	5070	100,100
180	14.31	14.52	15.01	14.56	14.38	14.50	14.97	14.57	170-180	1.364	5071	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:1
 Test Date:2019-08-16

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.412
 Humidity:65.0%
 Test Distance:9.650m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:220.19V I:0.2127A P:44.596W PF:0.9524 Freq:49.99Hz Lamp Flux:5071.25x1 lm		
NAME: L8989-NW45	TYPE:L8989-NW45	WEIGHT:
SPEC.:1228*89*89	DIM.: 1228*89*89	SERIAL No.:1#
MFR.: BLUEVISION	SUR.:1228*89	Shielding Angle:



LUMINANCE cd/(m2)		
G (DEG)	C0/180	C90/270
85	7882	249
80	9850	3428
75	11433	6014
70	12584	8018
65	13419	9551
60	14041	10702
55	14542	11622
50	14970	12385
45	15349	13055


C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:1
Test Date:2019-08-16

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.412
Humidity:65.0%
Test Distance:9.650m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:220.19V I:0.2127A P:44.596W PF:0.9524 Freq:49.99Hz Lamp Flux:5071.25x1 lm		
NAME: L8989-NW45	TYPE:L8989-NW45	WEIGHT:
SPEC.:1228*89*89	DIM.: 1228*89*89	SERIAL No.:1#
MFR.: BLUEVISION	SUR.:1228*89	Shielding Angle:

pcc	80%			70%			50%			30%			10%			0
p _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
p _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio															



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:1
Test Date:2019-08-16

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.412
Humidity:65.0%
Test Distance:9.650m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:220.19V I:0.2127A P:44.596W PF:0.9524 Freq:49.99Hz Lamp Flux:5071.25x1 lm					
NAME: L8989-NW45		TYPE:L8989-NW45		WEIGHT:	
SPEC.:1228*89*89		DIM.: 1228*89*89		SERIAL No.:1#	
MFR.: BLUEVISION		SUR.:1228*89		Shielding Angle:	

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients (WEC)										
0.0																	
1.0	.305	.174	.055	.298	.170	.054	.284	.163	.052	.272	.157	.050	.260	.151	.049		
2.0	.287	.158	.048	.281	.155	.048	.269	.149	.046	.258	.144	.045	.247	.140	.044		
3.0	.266	.142	.042	.260	.139	.042	.250	.135	.041	.240	.131	.040	.230	.128	.039		
4.0	.246	.128	.038	.241	.126	.037	.231	.123	.037	.222	.119	.036	.214	.116	.035		
5.0	.228	.116	.034	.223	.114	.033	.215	.112	.033	.207	.109	.032	.199	.106	.032		
6.0	.211	.106	.030	.207	.105	.030	.200	.102	.030	.192	.100	.029	.186	.098	.029		
7.0	.197	.097	.028	.193	.096	.027	.186	.094	.027	.180	.092	.027	.174	.090	.027		
8.0	.184	.090	.025	.181	.089	.025	.175	.087	.025	.169	.086	.025	.163	.084	.024		
9.0	.172	.083	.023	.169	.083	.023	.164	.081	.023	.159	.080	.023	.154	.078	.023		
10.0	.162	.078	.022	.160	.077	.021	.155	.076	.021	.150	.074	.021	.145	.073	.021		

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.198	.198	.198	.169	.169	.169	.115	.115	.115	.066	.066	.066	.021	.021	.021	
1.0	.187	.163	.142	.160	.140	.122	.110	.097	.085	.063	.056	.049	.020	.018	.016	
2.0	.179	.139	.106	.153	.120	.092	.105	.083	.064	.061	.048	.037	.019	.016	.012	
3.0	.171	.122	.082	.147	.105	.071	.101	.073	.050	.058	.043	.029	.019	.014	.010	
4.0	.163	.108	.066	.140	.094	.058	.096	.065	.041	.056	.038	.024	.018	.012	.008	
5.0	.156	.098	.055	.134	.085	.048	.092	.059	.034	.053	.035	.020	.017	.011	.007	
6.0	.149	.090	.047	.128	.078	.041	.088	.054	.029	.051	.032	.017	.017	.010	.006	
7.0	.142	.083	.041	.122	.072	.036	.084	.050	.025	.049	.030	.015	.016	.010	.005	
8.0	.136	.077	.036	.117	.067	.032	.081	.047	.023	.047	.028	.013	.015	.009	.004	
9.0	.130	.072	.033	.112	.062	.029	.077	.044	.020	.045	.026	.012	.015	.009	.004	
10.0	.124	.068	.030	.107	.059	.026	.074	.041	.019	.043	.024	.011	.014	.008	.004	

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:1
Test Date:2019-08-16

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.412
Humidity:65.0%
Test Distance:9.650m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:220.19V I:0.2127A P:44.596W PF:0.9524 Freq:49.99Hz Lamp Flux:5071.25x1 lm										
NAME: L8989-NW45					TYPE:L8989-NW45			WEIGHT:		
SPEC.:1228*89*89					DIM.: 1228*89*89			SERIAL No.:1#		
MFR.: BLUEVISION					SUR.:1228*89			Shielding Angle:		
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	15.9	17.4	16.2	17.6	17.9	14.9	16.4	15.2	16.6	16.8
3H	17.4	18.8	17.7	19.0	19.3	15.9	17.3	16.2	17.5	17.8
4H	18.0	19.3	18.3	19.5	19.8	16.2	17.5	16.5	17.7	18.0
6H	18.3	19.6	18.7	19.9	20.2	16.2	17.5	16.6	17.8	18.0
8H	18.4	19.6	18.8	19.9	20.2	16.2	17.4	16.6	17.7	18.0
12H	18.5	19.6	18.9	19.9	20.3	16.1	17.3	16.5	17.6	17.9
4H 2H	16.3	17.6	16.6	17.9	18.1	15.4	16.7	15.8	17.0	17.3
3H	17.9	19.0	18.2	19.3	19.7	16.6	17.7	16.9	18.0	18.4
4H	18.5	19.6	18.9	19.9	20.3	16.9	17.9	17.3	18.3	18.6
6H	19.0	19.9	19.4	20.3	20.7	17.0	17.9	17.4	18.3	18.7
8H	19.1	20.0	19.6	20.4	20.8	17.0	17.9	17.4	18.2	18.6
12H	19.2	20.0	19.7	20.4	20.8	16.9	17.7	17.4	18.1	18.6
8H 4H	18.6	19.4	19.0	19.8	20.2	17.0	17.9	17.5	18.3	18.7
6H	19.1	19.8	19.5	20.2	20.7	17.2	17.9	17.7	18.3	18.8
8H	19.3	19.9	19.7	20.4	20.8	17.2	17.8	17.7	18.3	18.7
12H	19.4	19.9	19.9	20.4	20.9	17.2	17.7	17.7	18.2	18.7
12H 4H	18.5	19.3	19.0	19.7	20.1	17.0	17.8	17.5	18.2	18.7
6H	19.1	19.7	19.5	20.1	20.6	17.2	17.8	17.7	18.3	18.8
8H	19.3	19.8	19.7	20.3	20.8	17.2	17.8	17.7	18.2	18.7
Variations with the observer position at spacings:										
S = 1.0H	+ 0.2 / - 0.2					+ 0.3 / - 0.3				
1.5H	+ 0.2 / - 0.2					+ 0.2 / - 0.3				
2.0H	+ 0.4 / - 0.6					+ 0.5 / - 0.4				

CIE Pub.117, 5071 lm Total Lamp Luminous Flux Correct (8log(F/F0) = 5.6)
Area: 0.109 m2

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:1
Test Date:2019-08-16

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.412
Humidity:65.0%
Test Distance:9.650m [K=1.0000]
Remarks:


```

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.412
Humidity:65.0%
Test Distance:9.650m [K=1.0000]
Remarks:

```

ISOCANDELA DIAGRAM

Test:U:220.19V I:0.2127A P:44.596W PF:0.9524 Freq:49.99Hz Lamp Flux:5071.25x1 lm		
NAME: L8989-NW45	TYPE:L8989-NW45	WEIGHT:
SPEC.:1228*89*89	DIM.: 1228*89*89	SERIAL No.:1#
MFR.: BLUEVISION	SUR.:1228*89	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:l
Test Date:2019-08-16

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.412
Humidity:65.0%
Test Distance:9.650m [K=1.0000]
Remarks:

AAI Figure

Test:U:220.19V I:0.2127A P:44.596W PF:0.9524 Freq:49.99Hz Lamp Flux:5071.25x1 lm		
NAME: L8989-NW45	TYPE:L8989-NW45	WEIGHT:
SPEC.:1228*89*89	DIM.: 1228*89*89	SERIAL No.:1#
MFR.: BLUEVISION	SUR.:1228*89	Shielding Angle:




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:1
Test Date:2019-08-16

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.412
Humidity:65.0%
Test Distance:9.650m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

Test:U:220.19V I:0.2127A P:44.596W PF:0.9524 Freq:49.99Hz Lamp Flux:5071.25x1 lm		
NAME: L8989-NW45	TYPE:L8989-NW45	WEIGHT:
SPEC.:1228*89*89	DIM.: 1228*89*89	SERIAL No.:1#
MFR.: BLUEVISION	SUR.:1228*89	Shielding Angle:



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:1
 Test Date:2019-08-16

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.412
 Humidity:65.0%
 Test Distance:9.650m [K=1.0000]
 Remarks:

LED Avg.L Report

Test:U:220.19V I:0.2127A P:44.596W PF:0.9524 Freq:49.99Hz Lamp Flux:5071.25x1 lm		
NAME: L8989-NW45	TYPE:L8989-NW45	WEIGHT:
SPEC.:1228*89*89	DIM.: 1228*89*89	SERIAL No.:1#
MFR.: BLUEVISION	SUR.:1228*89	Shielding Angle:


AvgL	cd/m2
L_0~180 (65) av	13251
L_0~180 (75) av	11217
L_0~180 (85) av	7543
L_90~270 (65) av	12872
L_90~270 (75) av	11087
L_90~270 (85) av	9624
L_45 (65) av	13044
L_45 (75) av	11136
L_45 (85) av	8477

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:1
 Test Date:2019-08-16

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.412
 Humidity:65.0%
 Test Distance:9.650m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: 1
Test Date: 2019-08-16

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.412
Humidity: 65.0%
Test Distance: 9.650m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:220.19V I:0.2127A P:44.596W PF:0.9524 Freq:49.99Hz Lamp Flux:5071.25x1 lm																	
NAME: L8989-NW45									TYPE:L8989-NW45						WEIGHT:		
SPEC.:1228*89*89									DIM.: 1228*89*89						SERIAL No.:1#		
MFR.: BLUEVISION									SUR.:1228*89						Shielding Angle:		

Table--1

UNIT: cd

C (DEG) γ (DEG)	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5			
0	1875	1875	1875	1875	1875	1875	1875	1875	1875	1875	1875	1875	1875	1875	1875	1875			
5	1866	1854	1843	1838	1840	1847	1857	1863	1863	1876	1886	1889	1887	1880	1872	1866			
10	1837	1812	1791	1781	1783	1798	1817	1831	1832	1855	1874	1882	1878	1864	1848	1836			
15	1788	1751	1720	1705	1708	1729	1758	1779	1781	1814	1842	1852	1847	1827	1803	1786			
20	1720	1674	1633	1613	1616	1643	1681	1709	1712	1755	1790	1801	1794	1769	1739	1719			
25	1637	1582	1532	1508	1511	1543	1589	1623	1626	1678	1718	1730	1722	1692	1658	1634			
30	1540	1476	1420	1392	1396	1431	1483	1523	1527	1586	1630	1644	1633	1599	1562	1536			
35	1430	1360	1298	1268	1272	1310	1367	1411	1416	1480	1528	1542	1530	1493	1453	1425			
40	1310	1236	1169	1138	1141	1182	1243	1290	1296	1364	1415	1428	1416	1377	1334	1305			
45	1182	1105	1035	1003	1007	1049	1113	1161	1168	1239	1291	1306	1293	1251	1208	1177			
50	1048	968	897	864	868	911	977	1027	1033	1107	1161	1176	1162	1120	1075	1042			
55	909	826	755	722	727	771	837	887	893	969	1025	1041	1027	984	937	903			
60	765	682	610	578	584	628	694	744	750	827	884	901	888	843	795	759			
65	618	535	464	434	440	484	550	598	603	681	739	758	746	700	650	613			
70	469	388	320	293	299	342	405	451	455	533	593	613	601	555	504	465			
75	322	247	187	163	170	207	265	308	311	385	446	467	456	410	359	319			
80	186	122	76.4	59.7	64.9	92.7	139	174	176	244	302	323	313	269	221	184			
85	74.8	32.9	6.04	2.36	2.37	16.0	44.8	67.5	68.5	120	169	189	180	143	102	73.8			
90	3.86	2.51	2.67	2.75	2.59	2.51	2.51	2.95	2.05	32.6	64.2	78.5	72.4	46.6	21.8	4.19			
95	2.67	3.11	3.34	3.43	3.26	3.11	2.82	2.73	2.61	2.26	2.69	6.94	3.94	2.02	2.23	2.40			
100	3.37	3.83	4.08	4.18	4.00	3.84	3.51	3.42	3.32	2.81	2.52	2.26	2.28	2.45	2.85	3.06			
105	4.14	4.60	4.87	4.99	4.80	4.62	4.29	4.19	4.09	3.49	3.14	2.86	2.90	3.11	3.53	3.80			
110	4.97	5.40	5.69	5.82	5.65	5.45	5.11	5.01	4.89	4.23	3.85	3.55	3.59	3.83	4.27	4.57			
115	5.81	6.26	6.54	6.70	6.54	6.32	5.97	5.85	5.70	5.00	4.58	4.27	4.34	4.60	5.06	5.37			
120	6.71	7.16	7.44	7.62	7.45	7.23	6.87	6.75	6.56	5.78	5.34	5.05	5.11	5.39	5.87	6.19			
125	7.61	8.09	8.35	8.52	8.38	8.19	7.79	7.69	7.44	6.63	6.18	5.85	5.92	6.24	6.72	7.09			
130	8.49	8.99	9.22	9.38	9.22	9.09	8.71	8.61	8.36	7.54	7.07	6.73	6.79	7.13	7.61	8.01			
135	9.36	9.86	10.1	10.2	10.1	9.99	9.64	9.52	9.22	8.44	7.99	7.65	7.67	8.03	8.50	8.87			
140	10.2	10.7	10.9	11.0	10.9	10.9	10.5	10.4	10.1	9.32	8.89	8.56	8.54	8.89	9.37	9.72			
145	11.0	11.5	11.7	11.8	11.6	11.7	11.3	11.2	10.9	10.2	9.84	9.56	9.47	9.81	10.3	10.6			
150	11.8	12.2	12.4	12.5	12.4	12.5	12.1	12.0	11.6	11.0	10.7	10.5	10.4	10.7	11.1	11.4			
155	12.4	12.8	13.0	13.1	13.1	13.2	12.8	12.7	12.3	11.8	11.6	11.4	11.3	11.5	11.8	12.0			
160	13.0	13.4	13.5	13.6	13.7	13.8	13.4	13.2	12.9	12.4	12.3	12.2	12.1	12.3	12.5	12.7			
165	13.5	13.8	14.0	14.1	14.3	14.3	13.9	13.7	13.4	13.1	13.0	13.0	13.0	13.0	13.2	13.2			
170	13.9	14.2	14.3	14.5	14.8	14.7	14.2	14.1	13.9	13.7	13.7	13.7	13.8	13.7	13.8	13.8			
175	14.2	14.4	14.5	14.7	15.0	14.8	14.5	14.4	14.2	14.1	14.2	14.3	14.5	14.3	14.3	14.2			
180	14.3	14.4	14.5	14.6	15.0	14.7	14.6	14.5	14.4	14.4	14.5	14.6	15.0	14.7	14.6	14.4			

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:1
Test Date:2019-08-16

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.412
Humidity:65.0%
Test Distance:9.650m [K=1.0000]
Remarks: