
1 H6 P Integrated Harness





- All Certified PV Connectors and Cables Available
- Standard Fuse Size up to 50A
- Resistance welded joints
- UV Resistant

Product Overview



H6 P Series Harness





NIU Power H6 P Branch Harness use high quality materials that guarantee long-term reliability. H6 Branch Harness have IP68 water-proof rating and can be used in a wide operating temperature range from -40 °C to 85 °C. NIU Power H6 P Branch Harness reduces the specialized labor required in your installation, making the integration of solar panels a breeze. With harnesses custom manufactured for your specific site, both labor and material costs are significantly reduced. The simplified design and robust construction also increase reliability, making the Interconnect System a perfect solution for any project.

Technical Data

Rated Voltage	DC 1500V			
Junction Rated Current	Max 70A			
Max Input Rated Current Protection in Strings	Max 32A			
Max Output Rated Current Protection in Bus	Max 50A			
Ambient temperature	IEC: -40 °C up to +85 °C			
Contact Resistance	≤ 0.05mΩ			
Pollution Degree	Class II			
Protection Degree	Class II			
Fire Resistance	UL94-V0			
Rated Impulse Voltage	16KV			
Locking System	NEC Locking Type			

Order Data

ТҮРЕ	1500V Cable Spec	Input String Fuse	Output Bus Fuse	Connectors
H6 nP P	Input: n Branch; Output: 1 Branch	n x Max 32A	Option:	Option: All Brando Salar connectors
H6 nP N	Cable:2.5mm ² ~16mm ² / 14AWG~6AWG	n x Max 32A	1x Max 50A	Option: All Brands Solar connectors

Remark: H series harnesses use high quality weather resistance materials that guarantee long-term reliability. H series Harnesses could match 2.5 mm² to 240 mm² cables, it could be wildly used in different applications. H series harnesses have IP68 water-proof rating and can be used in a wide operating temperature range from -40 °C to 85 °C.

