

A4 A Series Al Cable Solar Connector

A4 A 系列铝线光伏连接器

new

A4 A Series Al Connector



DC 1500V, Al Cable Connector



IEC 1500V / UL 1500V



IEC: 62852 / UL: 6703



-40°C~90°C



UL94-V0



IP 68



UV Resistance

型号 TYPE	线缆规格 Cable Spec	线缆外径 OD	电压 Voltage	电流 Current
A4-A-F	6mm ² ~16mm ²	6.0mm~10mm	1500V	30A~60A
A4-A-M	6mm ² ~16mm ²	6.0mm~10mm	1500V	30A~60A



接组串或逆变器
To String or inverter



Solar Al Cable 光伏铝线



接组串或逆变器
To String or inverter

A6 A Series Al-Cu Cable Adaptor

A6 A 系列光伏铝线铜线转接器

A6-A Solar Al-Cu Adapter



DC 1500V, Panel Connector



IEC 1500V / UL 1500V



IEC: 62852



-40°C~90°C



UL94-V0



IP 68



UV Resistance

型号 TYPE	线缆规格 Cable Spec	线缆外径 OD	电压 Voltage	电流 Current
A6-A	2.5mm ² ~16mm ²	4.7mm~10mm	1500V	30A~60A

铜线 Copper Cable



铝线 Al Cable

IP 68 光伏铜铝线转接器

IP 68 Solar Al-Cu cable Adaptor

Remark 备注:

Al-Cu cable connectors use high quality weather resistance materials that guarantee long-term reliability. The products could match 2.5mm² to 16mm² cables, they could be widely used in different applications. They have IP68 water-proof rating and can be used in a wide operating temperature range from -40 °C to 90 °C.

铜铝连接器采用高品质绝缘耐候材料, 可保障产品在户外长期安全使用。产品可适配 2.5 平方到 16 平方电线, 具有更广的应用范围。铜铝系列连接器符合 IP68 额定标准, 且能够工作在-40 °C 到 90 °C 极限环境。

