

**TCB****GRANT OF EQUIPMENT  
AUTHORIZATION****TCB**

**Certification**  
**Issued Under the Authority of the**  
**Federal Communications Commission**  
**By:**

**Bay Area Compliance Laboratory Corp.**  
**1274 Anvilwood Avenue**  
**Sunnyvale, CA 94089**

**Date of Grant: 06/03/2020**  
**Application Dated: 06/03/2020**

**Hangzhou Roombanker Technology Co., Ltd.**  
**A#801 Wantong center,**  
**Hangzhou,**  
**China**

**Attention: Lin Su**

**NOT TRANSFERABLE**

EQUIPMENT AUTHORIZATION is hereby issued to the named GRANTEE, and is VALID ONLY for the equipment identified hereon for use under the Commission's Rules and Regulations listed below.

**FCC IDENTIFIER:** 2AUXBD SGW-040  
**Name of Grantee:** Hangzhou Roombanker Technology Co., Ltd.  
**Equipment Class:** Digital Transmission System  
**Notes:** L-Serial Smart Gateway

<u>Grant Notes</u>	<u>FCC Rule Parts</u>	<u>Frequency Range (MHZ)</u>	<u>Output Watts</u>	<u>Frequency Tolerance</u>	<u>Emission Designator</u>
	<b>15C</b>	<b>2402.0 - 2480.0</b>	<b>0.001</b>		
	<b>15C</b>	<b>2405.0 - 2480.0</b>	<b>0.081</b>		
<b>MO</b>	<b>15C</b>	<b>2412.0 - 2462.0</b>	<b>0.15</b>		

Output power listed is conducted. The device contains an approved module (FCC ID: XMR201707BG96) documented in this filing. The antenna(s) used for this transmitter must be used to provide a separation distance of at least 20 cm from all persons and must not be co-located or operating in conjunction with any other antenna or transmitter, except in accordance with FCC multi-transmitter product procedures. End-users must be provided with antenna installation instructions and transmitter operating conditions for satisfying RF exposure compliance. This product supports 20 MHz and 40 MHz bandwidth modes.

MO: This Multiple Input Multiple Output (MIMO) device was evaluated for multiple transmitted signals as indicated in the filing.