



浙江鸿森机械有限公司

ZHEJIANG HONGSEN MACHINERY CO.,LTD



地址：浙江省诸暨市店口镇制冷工业园区
826-827号

ADD: #826-827 Diankou refrigeration industrial park, Zhuji city,
Zhejiang province

网址 /WEB: www.zjhsjx.com



电话 /TEL: 0575-87696107 0575-87607883
0575-87608106

传真 /FAX: 0575-87698985

E-mail: hongsen@zjhsjx.com hongsen6@zjhsjx.com
zhongsen@163.com

HONGSEN 鸿森

2024

空调专业维修工具

HVAC&R SERVICE TOOLS

2024 HVAC&R SERVICE TOOLS

鸿森·空调专业维修工具

HONGSEN MACHINERY

Escort For Safe Refrigeration



CONTENTS

目录

11-40

表组系列

Manifold Gauge Series

41-45

快速接头系列

Quick Coupler Series

47-48

加注阀系列

Charging Valve Series

49-61

其他工具

Other Tools

62-63

配件系列

Other Fittings

HONGSEN

ESCORT FOR
SAFE REFRIGERATION

关于鸿森

ABOUT HONGSEN

鸿森人有着对产品的匠人匠心精神，借助现代化高精尖设备和技术，做好每一款产品。

鸿森机械有限公司创建于1992年，一直潜心致力于制冷空调用各类阀门的开发、研究和制造。30年来，鸿森人“开拓进取，永不满足”的执着追求，坚持以高新技术为发展方向，坚持走规模效益、质量效益的可持续发展之路。

公司占地面积50000平方米，拥有员工400多人，以及一支30多人的专业技术团队，年生产能力2000万件。在浙江大学、上海交通大学和西安交通大学等高校专家的指导下，聘请国内著名主机企业的技术行家为顾问，为企业培育了一批强有力的生产、技术和质量的精英，公司主要生产电子膨胀阀系列、电动调节阀系列、电磁阀系列、球阀系列、视液镜系列、膨胀阀系列、截止阀系列、避震管系列、过滤器系列等多种产品，逐步发展为一体化生产企业。

Hongsen people have the spirit of craftsmanship, with the help of modern high-end equipment and technology, do every product well.

Zhejiang Hongsen Machinery Co., Ltd was founded in 1992, which devotes itself in the R&D and manufacture of various valves in refrigeration and air conditioning system. For 30 years, Hongsen Machinery staffs persistently adhere to open up, keep forging ahead and never rest content with their achievements. They insist on new and high-tech as the guidance in the development and pursue the sustainable development road with high productivity and quality efficiency.

Hongsen Machinery covers a land area of 50,000 square meters. There are over 400 staffs and workers including a specialty team of 30 technicians. Hongsen Machinery has a close cooperation with the professors and experts in Zhejiang University, Shanghai Jiao Tong University and Xian Jiao Tong University and several senior engineers of leading domestic OEMs are invited as the consultants of the company. A number of technical talents are trained in production, development and quality control and grow up in the company. At present, Hongsen Machinery is capable to manufacture multiple categories of refrigeration and A/C accessory parts such as electric expansion valve series, motorized regulating valve series, solenoid valve series, ball valve series, sight glass series, expansion valve series and shut off valve series. Hongsen Machinery becomes one company integrating R&D, production and marketing into one.



智能生产线
ADVANCED PRODUCTION LINE

国内领先技术
自动化生产


半自动红外线节能烘箱
SEMI-AUTOMATIC INFRARED ENERGY-SAVING OVEN

高效节能
操作便捷



精加工车间
FINISHING CENTER

高精尖加工中心
CNC数控



氦气检漏设备
HELUM TESTING MACHINE

自动检漏报警
检测效率极高

氦气检漏设备
HELUM TESTING MACHINE

高效精准
环保安全



每一款产品的背后
是高精技术的匠心打造


FOCUS ON REFRIGERATION FOR 30 YEARS

公司下设三个事业部：空调工具事业部、自控元件事业部和环境设备事业部，拥
有国内先进的CNC加工设备及高端检测设备300余台（套）。

Hongsen has three production divisions: A/C tooling, Refrigeration
Control parts and Environmental equipment, with the support more than
300 sets of inspecting equipments and advanced CNC equipments.

发展历程

DEVELOPMENT HISTORY



全球品牌渠道

GLOBAL BRAND CHANNELS



MANIFOLD GAUGE SET

表组系列



表组系列 MANIFOLD GAUGE SET

HS-DVS60/HS-D480



产品特点 Product Characteristics

电子表 Digital gauge

- 高精度数字显示 High precision digital display
- 操作简便 Simple operation

外壳 Protective housing

- 防撞设计 Anti-collision design

手轮 Knob

- 球阀式结构, 操作便捷, 精准加注 Ball valve design, easier operation and more precise charging.
- 符合人体功能学的手轮, 舒适耐用 Gentle and comfortable knob

挂钩 Hook

- 折叠挂钩 Foldable hook
- 便于收纳 Easy storage and hiding

视液镜 Liquid indicator

- 防爆视液镜 Explosion-proof liquid indicator

选型 Model selection



HS-DVS60-101A HS-D480AH HS-D480AL HS-D5300

选型表 Model selection

型号 Model	压力表 Pressure gauge				加液管 Refrigerant charging hose	额外配置 Accessories		
	制冷剂 Refrigerant	表盘大小 Diameter	压力单位 Pres.unit	温度单位 Temp.unit		快速接头 Quick coupler	包装 Package	其他 Other
HS-DVS60-101A-60	R22 R134a R1234yf R32 R407C R404A R410A R507 R600a	—	psi/bar/Mpa/Kpa	°C/°F	60" 800~4000psi"	/	皮箱 Plastic case	Charging control valve*2 5/16SAE*1/4SAE
HS-DVS60-101A-72	R22 R134a R1234yf R32 R407C R404A R410A R507 R600a	—	psi/bar/Mpa/Kpa	°C/°F	72" 800~4000psi"	/	皮箱 Plastic case	Charging control valve*2 5/16SAE*1/4SAE

· 三色管3根(红色、黄色、蓝色), 接口为1/4SAE

· 所有阀体上的接口为1/4SAE

· Charging hoses 3 pcs(red,yellow,blue), all 1/4SAE connection

· Thread of all adapter on valve: 1/4SAE

选型表 Model selection

型号 Model	压力表 Pressure gauge				加液管 Refrigerant charging hose	额外配置 Accessories		
	制冷剂 Refrigerant	表盘大小 Diameter	压力单位 Pres.unit	温度单位 Temp.unit		快速接头 Quick coupler	包装 Package	其他 Other
HS-D480AH-36	R22 R134a R1234yf R32 R407C R404A R410A R507 R600a	—	psi/bar/Mpa/Kpa	°C/°F	36" 800~4000psi	/	皮箱 Plastic case	R410A转换接头*1 R410A adapter*1
HS-D480AH-60	R22 R134a R1234yf R32 R407C R404A R410A R507 R600a	—	psi/bar/Mpa/Kpa	°C/°F	60" 800~4000psi	/	皮箱 Plastic case	R410A转换接头*1 R410A adapter*1
HS-D480AH-72	R22 R134a R1234yf R32 R407C R404A R410A R507 R600a	—	psi/bar/Mpa/Kpa	°C/°F	72" 800~4000psi	/	皮箱 Plastic case	R410A转换接头*1 R410A adapter*1
HS-D480AL-36	R22 R134a R1234yf R32 R407C R404A R410A R507 R600a	—	psi/bar/Mpa/Kpa	°C/°F	36" 800~4000psi	/	皮箱 Plastic case	R410A转换接头*1 R410A adapter*1
HS-D480AL-60	R22 R134a R1234yf R32 R407C R404A R410A R507 R600a	—	psi/bar/Mpa/Kpa	°C/°F	60" 800~4000psi	/	皮箱 Plastic case	R410A转换接头*1 R410A adapter*1
HS-D480AL-72	R22 R134a R1234yf R32 R407C R404A R410A R507 R600a	—	psi/bar/Mpa/Kpa	°C/°F	72" 800~4000psi	/	皮箱 Plastic case	R410A转换接头*1 R410A adapter*1
HS-D5300	R22 R134a R1234yf R32 R407C R404A R410A R507 R600a	—	psi/bar/Mpa/Kpa	°C/°F	/	/	纸盒 Paper box	/

· 三色管2根(AH配红色、黄色管子; AL配蓝色、黄色管子), 接口为1/4SAE

· 所有阀体上的接口为1/4SAE

· Charging hoses 2 pcs(AH with red, yellow hose; AL with blue, yellow hose), all 1/4SAE connection

· Thread of all adapter on valve: 1/4SAE

表组系列 MANIFOLD GAUGE SET

HS-MVS60/HS-M480



产品特点 Product Characteristics

电子表 Digital gauge

- 高精度冷媒表 High precision refrigerant gauge
- 操作简便 Simple operation

外壳 Protective housing

- 防撞设计 Anti-collision design

手轮 Knob

- 球阀式结构,操作便捷,精准加注 Ball valve design, easier operation and more precise charging.
- 符合人体功能学的手轮,舒适耐用 Gentle and comfortable knob

挂钩 Hook

- 折叠挂钩 Foldable hook
- 便于收纳 Easy storage and hiding

视液镜 Liquid indicator

- 防爆视液镜 Explosion-proof liquid indicator

选型 Model selection



选型表 Model selection

型号 Model	压力表 Pressure gauge				加液管 Refrigerant charging hose	额外配置 Accessories			
	制冷剂 Refrigerant	表盘大小 Diameter	压力单位 Pres.unit	温度单位 Temp.unit		快速接头 Quick coupler	螺丝刀 Screw driver	其他 Other	包装 Package
HS-MVS60-101A-60	R22 R134a R404A R410A	70mm(2-1/2")	psi/bar	°C	60" 800~4000psi	/	1 pc	R410A转换接头 *2 R410A adapter *2	皮箱 Plastic case
HS-MVS60-101A-72	R22 R134a R404A R410A	70mm(2-1/2")	psi/bar	°C	72" 800~4000psi	/	1 pc	R410A转换接头 *2 R410A adapter *2	皮箱 Plastic case
HS-MVS60-134-60A	R22 R134a R404A R410A	70mm(2-1/2")	psi/bar	°C	60" 800~4000psi	1. HS-MH 2. HS-ML	1 pc	取芯工具1只,开瓶器1只 Core remover *1 Can tap valve *1	皮箱 Plastic case
HS-MVS60-134-72A	R22 R134a R404A R410A	70mm(2-1/2")	psi/bar	°C	72" 800~4000psi	1. HS-MH 2. HS-ML	1 pc	取芯工具1只,开瓶器1只 Core remover *1 Can tap valve *1	皮箱 Plastic case

• 三色管3根(红色、黄色、蓝色),工作压力800psi,爆破压力4000psi,接口为1/4SAE
 • 所有阀体上的接口为1/4SAE
 • 塑料箱包装

• Charging hoses 3 pcs(red,yellow,blue), 800 psi working pres., 4000 psi
 bursting pres., all 1/4SAE connection
 • Thread of all adapter on valve: 1/4SAE
 • Plastic case packin

选型表 Model selection

型号 Model	压力表 Pressure gauge				加液管 Refrigerant charging hose	额外配置 Accessories			
	制冷剂 Refrigerant	表盘大小 Diameter	压力单位 Pres.unit	温度单位 Temp.unit		快速接头 Quick coupler	螺丝刀 Screw driver	其他 Other	包装 Package
HS-M480AH-36	R22 R134a R404A R410A	70mm(2-1/2")	psi/bar	°C	36" 800~4000psi	/	/	R410A转换接头 *1 R410A adapter *1	彩盒 Paper box
HS-M480AH-60	R22 R134a R404A R410A	70mm(2-1/2")	psi/bar	°C	60" 800~4000psi	/	/	R410A转换接头 *1 R410A adapter *1	彩盒 Paper box
HS-M480AH-72	R22 R134a R404A R410A	70mm(2-1/2")	psi/bar	°C	72" 800~4000psi	/	/	R410A转换接头 *1 R410A adapter *1	彩盒 Paper box
HS-M480AL-36	R22 R134a R404A R410A	70mm(2-1/2")	psi/bar	°C	36" 800~4000psi	/	/	R410A转换接头 *1 R410A adapter *1	彩盒 Paper box
HS-M480AL-60	R22 R134a R404A R410A	70mm(2-1/2")	psi/bar	°C	60" 800~4000psi	/	/	R410A转换接头 *1 R410A adapter *1	彩盒 Paper box
HS-M480AL-72	R22 R134a R404A R410A	70mm(2-1/2")	psi/bar	°C	72" 800~4000psi	/	/	R410A转换接头 *1 R410A adapter *1	彩盒 Paper box

• 三色管2根(AH配红色、黄色管子; AL配蓝色、黄色管子),接口为1/4SAE
 • 所有阀体上的接口为1/4SAE

• Charging hoses 2 pcs(AH with red, yellow hose; AL with blue, yellow hose), all 1/4SAE connection
 • Thread of all adapter on valve: 1/4SAE

表组系列 MANIFOLD GAUGE SET

智能数字表 HS-330



技术参数 Technical Parameters

压力测试 Pressure value: 表压 gauge pressure

压力测试单位 Pressure unit: Kpa; MPa; bar; inHg; Psi.

压力测试量程 Pressure range: 0Kpa~6000Kpa

压力测试精度 Accuracy: ±0.5% (FS) +5dgt

压力过载极限 Overload Pressure limit: 10000Kpa (10MPa; 100bar)

温度测试单位 Temperature unit: °C/°F

温度测试量程 Temperature range: -40°C~150°C (-40°F~302°F)

温度测试精度 Temperature accuracy: ±0.5°C +2dgt

±0.9°F +2dgt

供电电源 Power Supply: 4×1.5V

接口 Connector: 1/4SAE

真空度测试 Vacuum value: 相对真空气

真空度测试单位 Vacuum unit: Kpa; MPa; bar; inHg; Psi.

真空度测试量程 Vacuum range: -101Kpa~0Kpa

适用工质 Refrigerant(89): R11 R113 R114 R115 R116 R12 R123 R124 R125 R1270 R13 R134A R14 R141B R142B R143A R152A R170 R21 R218 R22 R227EA R23 R236EA R245CA R245FA R290 R32 R401A R401B R401C R402A R402B R403A R403B R404 R405A R406A R407A R407B R407C R407D R407E R408A R409A R409B R41 R410A R410B R411A R411B R412A R413A R414A R414B R415A R415B R416A R417A R418A R419A R420A R421A R421B R422A R422B R422C R422D R423A R424A R425A R426A R427A R428A R50 R500 R501 R502 R503 R504 R507A R508A R508B R509A AR600 R600A R717 R744 (Co₂) 1234yf

产品特点 Product Characteristics

- 外壳采用高强度工程塑料成型，整机坚固结实
- 柔性防滑硅胶设计，握持舒适
- 高精度数据采集单元，数据稳定精准
- 背光设计，方便弱光处操作
- 微功耗电子元件，延长电池寿命
- 内置89种冷媒数据库，参数齐全
- 双通道实时温度测量，精准、方便
- 多模式选择，功能齐全
- 折叠挂钩，便于收纳
- 优质铝合金阀组，经久耐用
- 防爆视窗，安全可靠。
- High-strength engineering plastics applied for the housing, make it strong and solid.
- Flexible non-slip silicone design, comfortable to hold.
- High-precision data acquisition unit, stable and accurate.
- Backlight design, easy to operate in low light.
- Micro-power electronics, to extend battery life.
- Built-in 89 kinds of refrigerant database, complete parameters.
- Dual-channel real-time temperature measurement, accurate and convenient.
- Multi-mode selection, full-featured.
- Folding hook, easy to storage.
- High-quality aluminum alloy valve manifold, durable.
- Explosion-proof sight glass, safe and reliable.

表组系列 MANIFOLD GAUGE SET

HS-B60-R744

R744
CO₂



HS-B60-R744-A



HS-B60-R744-A-QC

产品特点 Product Characteristics

- 阀体
— 一体式铜阀结构, 性能优越
- 手轮
符合人体功能学的铝制手轮, 舒适耐用
- 泄压结构, 可手动排气
- 超强耐压性能, 安全可靠

- Valve body
Integrated copper valve structure, superior performance
- Handwheel
Ergonomic aluminum handwheel, comfortable and durable
- Pressure relief structure, manual exhaust
- Super pressure resistance, safe and reliable

选型 Model selection



- 双层钢网, 超高耐压, 爆破压力≥8700Psi (60MPa)
- 硬密封接口, 安全可靠
- SUS304配件, 使用寿命更长
- 8角液压, 受力均匀, 加强密封
- 保护弹簧, 有效保护管体两端
- Double-layer steel mesh, ultra-high pressure resistance, burst pressure ≥8700Psi (60MPa)
- Hard sealed interface, safe and reliable
- SUS304 accessories, longer service life
- 8 angle hydraulic mounting, uniform force, strengthened sealing
- Protective spring, effectively protect both ends of the hose

选型表 Model selection

型号 Model	制冷剂 Refrigerant	工作压力 Working pressure	爆破压力 Bursting pressure	长度 Length	接口 Connection
HS-360-R744	R744(CO ₂)	120bar	600bar	60"	1/4SAE-1/4SAE
HS-372-R744				72"	1/4SAE-1/4SAE



- 符合J639标准
- 自锁结构, 环保可靠
- 开度可调, 精准加注
- 一体式阀体结构, 超高耐压, 爆破压力≥8700Psi (60MPa)

- Meet the J639 standard
- Self-locking structure, environmental protection and reliable
- Adjustable opening, precise filling
- One-piece valve body structure, ultra-high pressure resistance, burst pressure ≥8700Psi (60MPa)



选型表 Model selection


型号 Model	压力表 Pressure gauge				加液管 Refrigerant charging hose	额外配置 Accessories			
	制冷剂 Refrigerant	表盘大小 Diameter	压力单位 Pres.unit	温度单位 Temp.unit		快速接头 Quick coupler	螺丝刀 Screw driver	其他 Other	包装 Package
HS-B60-R744-A	R744(CO ₂)	80mm(3-1/8")	psi/Mpa	/	60" 120-600bar	/	/	/	铝箱 Aluminium case
HS-B60-R744-A-QC	R744(CO ₂)	80mm(3-1/8")	psi/Mpa	/	60" 120-600bar	1.HS-MH-R744 2.HS-ML-R744	/	/	铝箱 Aluminium case"

选型表 Model selection

型号 Model	制冷剂 Refrigerant	接口 Connection	类型 Type	备注 Remark
HS-MH-R744	R744 (CO ₂)	1/4SAE	手动型 Manual type	高压high side
HS-ML-R744		1/4SAE	手动型 Manual type	低压low side

表组系列 MANIFOLD GAUGE SET

HS-M01/HS-M02



(小巧便携)

产品特点 Product Characteristics

- 精致小巧,外形精美
- 滚压视窗,安全美观
- 球阀结构,开关方便快捷
- 人体功能学手轮,舒适耐用
- 皮箱包装:方便收纳和携带

- Exquisite and small, beautiful appearance
- Rolling Sight glass, safe and beautiful
- Ball valve structure, convenient and fast switching
- Gentle and comfortable aluminum knob
- Plastic box package:easy to store and carry



工具套件
高档皮箱包装
方便收纳和携带

工具套件
塑封盒
经济实用



Tool kit
High-end plastic-case packaging
Convenient storage, easy carry

Tool kit
Paper box
economical and practical



选型 Model selection



HS-M01	HS-M01-134-A	HS-M02	HS-M02-410-22-A
--------	--------------	--------	-----------------

选型表 Model selection

型号 Model	压力表 Pressure gauge				加液管 Refrigerant charging hose	额外配置 Accessories		
	制冷剂 Refrigerant	表盘大小 Diameter	压力单位 Pres.unit	温度单位 Temp.unit		快速接头 Quick coupler	其他 Other	包装 Package
HS-M01	R134a R1234yf R22	50mm(1-15/16")	Psi/bar	°C	/	/	/	泡壳 Blister Packing
HS-M02	R22 R410A R32	50mm(1-15/16")	Psi/bar	°C	/	/	/	泡壳 Blister Packing
HS-M01-134-A	R134a R1234yf R22	50mm(1-15/16")	Psi/bar	°C	48" 600-3000Psi	1.HS-MH 2.HS-ML	取芯工具1只 HS-339开瓶器1只 1 pic of core remover 1 pic of HS-339 can tap valve	皮箱 Plastic case
HS-M02-410-22-A	R22 R410A R32	50mm(1-15/16")	Psi/bar	°C	48" 600-3000Psi	/	HS-R410A转换接头2只 with 2 pcs of HS-R410A adapters	皮箱 Plastic case

表组系列 MANIFOLD GAUGE SET 智能数字表 HS-370



制冷剂
93种

HS/370-A

技术参数 Technical Parameters

压力测试 Pressure value: 表压 gauge pressure

压力测试单位 Pressure unit: Kpa; MPa; bar; inHg; Psi.

压力测试量程 Pressure range: 0Kpa~6000Kpa

压力测试精度 Accuracy: ±0.5%(FS)+5dgt

压力过载极限 Overload Pressure limit: 10000Kpa (10MPa; 100bar)

温度测试单位 Temperature unit: °C/°F

温度测试量程 Temperature range: -40°C~150°C (-40°F~302°F)

温度测试精度 Temperature accuracy: ±0.5°C+2dgt

±0.9°F +2dgt

真空度测试 Vacuum value: 相对真空度

真空度测试单位 Vacuum unit: Kpa; MPa; bar; inHg; Psi.

真空度测试量程 Vacuum range: -101Kpa~0Kpa

供电电源 Power Supply: 4×1.5V 接口 Connector: 1/4 SAE

配置:

- HS/TS-1500 测温夹: 两只
- HS/可调节快速接头: 一套
- HS/R410A转换接头: 两只
- HS/1.5米三色管: 一套
- 5号电池: 4节

适用工质 Refrigerant(93): R11 R113 R114 R115 R116 R12 R123 R124 R125 R1270 R13 R134A R14 R141B R142B R143A R152A R170 R21 R218 R22 R227EA R23 R236EA R245CA R245FA R290 R32 R401A R401B R401C R402A R402B R403A R403B R404A R405A R406A R407A R407B R407C R407D R407E R408A R409A R409BR41 R410A R410B R411A R411B R412A R413A R414A R414B R415A R415B R416A R417A R418A R419A R420A R421A R421B R422A R422B R422C R422D R423A R424A R425A R426A R427A R428A R438A R448A R449A R452A R50 R500 R501 R502 R503 R504 R507A R508A R508B R509A R600 R600A R717 R744(Co2) R1234yf

Accessories:

- HS/TS-1500 temperature sensor: 2pcs
- HS/Quick coupler: 1set
- HS/R410A adapter: 2pcs
- HS/1.5M charging hose: 1set
- 5# battery: 4pcs

产品特点 Product Characteristics

- 外壳采用高强度工程塑料成型, 整机坚固结实
- 柔性防滑硅胶设计, 握持舒适
- 高精度数据采集单元, 数据稳定精准
- 背光设计, 方便弱光处操作
- 微功耗电子元件, 延长电池寿命
- 内置93种冷媒数据库, 参数齐全
- 双通道实时温度测量, 精准、方便
- 多模式选择, 功能齐全
- 折叠挂钩, 便于收纳
- 优质铝合金阀组, 经久耐用
- 防爆视窗, 安全可靠

- High-strength engineering plastics applied for the housing, make it strong and solid.
- Flexible non-slip silicone design, comfortable to hold.
- High-precision data acquisition unit, stable and accurate.
- Backlight design, easy to operate in low light.
- Micro-power electronics, to extend battery life.
- Built-in 93 kinds of refrigerant database, complete parameters.
- Dual-channel real-time temperature measurement, accurate and convenient.
- Multi-mode selection, full-featured.
- Folding hook, easy to storage.
- High-quality aluminum alloy valve manifold, durable.
- Explosion-proof sight glass, safe and reliable.

测温夹 TEMPERATURE MEASURING CLAMP HS-TS-1500



技术参数 Technical Parameters

温度测试单位 Temperature unit: °C/°F

温度测试量程 Temperature range: -40°C~150°C (-40°F~302°F)

温度测试精度 Temperature accuracy: ±0.5°C+2dgt

±0.9°F +2dgt


传感器线长 The length of sensor wire: 1.5m

产品特点 Product Characteristics

- 外壳采用高强工程塑料成型, 坚固结实
- 传感器精度高, 测量精准
- 弹性钳口, 方便实用
- The shell uses high-strength engineering plastics the whole machine is solid.
- High precision sensor, accurate measurement.
- Flexible jaws, convenient and practical.

压力表 Pressure Gauge

选型 Model selection



213#H



213#L



211#H



211#L



201#H



201#L



200#H



200#L

产品特点 Product Characteristics

- 防跳针设计
- 配置校准螺母
- 各种制冷剂、压力单位、温度单位均可接受定制

- No-flutter gauge design
- With Front calibration access port
- Various refrigerants, pressure units, and temperature units can be customized

选型表 Model selection

型号 Model	制冷剂 Refrigerant	尺寸 Dial	压力单位 Pres.unit	温度单位 Temp.unit	接口 Connector
213# H	R404A R407C R22 R134a	70mm(2-1/2")	psi/bar	°C	1/8NPT
213# L					
211# H	R410A R22 R134a R404A	80mm(3-1/8")	psi/bar	°C	1/8NPT
211# L					
201# H	R404A R407C R22 R134a	80mm(3-1/8")	psi/bar	°C	1/8NPT
201# L					
200# H	R32 R410A	80mm(3-1/8")	psi/bar	°C	1/8NPT
200# L					

充油(真空)压力表 Oil-filled (vacuum) pressure Gauge



242#H 242#L 128#H 128#L 191#H 191#L



122#H 122#L 59#H 59#L

氮气保压表 Flex Hose With Valve Gauge For Nitrogen



产品特点 Product Characteristics

- 具有三类不同制冷剂系统的保压试漏的压力指示功能
- 具有充氮清理管路,充氮保护焊接管路的压力指示功能
- 小球阀,方便控制压力输出
- 红色指针用于标识输入时压力值

- Indicate the pressure during the leaking test under pressure
- Indicate the pressure during the flushing or nitrogen protection welding
- Mini ball valve, easy to control pressure output
- The red pointer can be used to record the input pressure.


选型表 Model selection						
型号 Model	制冷剂 Refrigerant	充油 Oil	尺寸 Dial	压力单位 Pres.unit	温度单位 Temp.unit	接口 Connector
242# H	R404A R407C R22 R134a	甘油 glycerin	63mm	psi/Mpa	°C	1/4SAE
242# L	R404A R407C R22 R134a		63mm	psi/Mpa		
128# H	R410A	硅油 Silicone oil	63mm	psi, Kg/cm3	°C	1/4SAE
128# L	R410A		63mm	psi, Kg/cm3		
191# H	R404A R407C R22 R134a	硅油 Silicone oil	63mm	Mpa	°C	1/4SAE
191# L	R404A R407C R22 R134a		63mm	Mpa		
122# H	R404A R407C R22 R134a	甘油 glycerin	63mm	Mpa psi	°C	1/4SAE
122# L	R404A R407C R22 R134a		63mm	Mpa psi		
59# H	R404A R407C R22 R134a	—	63mm	psi/Mpa	°C	1/4SAE
59# L	R404A R407C R22 R134a	—	63mm	psi/Mpa		

选型表 Model selection					
型号 Model	适用介质 Applicable media	接口 Connector	尺寸 Dial	压力单位 Pres.unit	压力量程 Pressure range
HS-NG	R134a R404A R407C R507 R22 R410A 氮气 Nitrogen gas	1/4SAE	80mm (3-1/8")	bar	-1 bar ~ 60 bar

表组系列 MANIFOLD GAUGE SET

HS-468AH / HS-468AL

工具套件 Tool kit
 彩盒 Paper box
 经济实用 economical and practical



选型 Model selection



HS-467AH	HS-467AL	HS-468AH	HS-468AL
----------	----------	----------	----------

产品特点 Product Characteristics

单表阀 Single manifold gauge

- 单表设计,经济实用
- Single meter design, economical and practical

手轮 Knob


- 符合人体功能学的铝制手轮,舒适耐用
- Gentle and comfortable aluminium knob

型号 Model	压力表 Pressure gauge				加液管 Refrigerant charging hose	额外配置 Accessories		
	制冷剂 Refrigerant	表盘大小 Diameter	压力单位 Pres.unit	温度单位 Temp.unit		快速接头 Quick coupler	其他 Other	包装 Package
HS-467AH	R12 R22 R404A R134a	70mm(2-1/2")	psi kg/cm ²	°C	/	/	/	彩盒 Paper box
HS-467AL	R12 R22 R404A R134a	70mm(2-1/2")	psi kg/cm ²	°C	/	/	/	彩盒 Paper box
HS-468AH	R32 R410A	80mm(3-1/8")	psi/bar	°C	/	/	/	彩盒 Paper box
HS-468AL	R32 R410A	80mm(3-1/8")	psi/bar	°C	/	/	/	彩盒 Paper box

表组系列 MANIFOLD GAUGE SET

HS-S36F-1234

R1234yf



产品特点 Product Characteristics

阀体 Valve body

- 紧凑的阀体设计，便捷易携
Compact valve body design, convenient and easy to carry

视液镜 Liquid indicator

- 防爆视液镜 Explosion-proof liquid indicator

手轮 Knob

- 符合人体功能学的铝制手轮，舒适耐用
Gentle and comfortable aluminium knob


选型表 Model selection

型号 Model	压力表 Pressure gauge				加液管 Refrigerant charging hose	额外配置 Accessories			
	制冷剂 Refrigerant	表盘大小 Diameter	压力单位 Pres.unit	温度单位 Temp.unit		快速接头 Quick coupler	螺丝刀 Screw driver	其他 Other	包装 Package
HS-S36F-1234	R1234yf	80mm(3-1/8")	psi/bar	°C/°F	60" 800~4000psi	1.HS-MH-1234 2.HS-ML-1234	1 pic	取芯工具1只 Core remover *1	皮箱 Plastic case



表组系列 MANIFOLD GAUGE SET

HS-S60



产品特点 Product Characteristics

外壳 Protective housing

- 防撞设计 Anti-collision design

视液镜 Liquid indicator

- 防爆视液镜 Explosion-proof liquid indicator

手轮 Knob

- 符合人体功能学的铝制手轮, 舒适耐用 Gentle and comfortable aluminium knob



工具套件
高档皮箱包装
方便收纳和携带

Tool kit
High-end plastic-case packaging
Convenient storage, easy carry

工具套件
彩盒
经济实用

Tool kit
Paper box
economical and practical



选型 Model selection



HS-S60-101




HS-S60-102

选型表 Model selection

型号 Model	压力表 Pressure gauge				加液管 Refrigerant charging hose	额外配置 Accessories		
	制冷剂 Refrigerant	表盘大小 Diameter	压力单位 Pres.unit	温度单位 Temp.unit		快速接头 Quick coupler	螺丝刀 Screw driver	其他 Other
HS-S60-101-60	R22 R404A R134a R407C	3-1/8" (80mm)	psi/bar	°C	60" 600~3000psi	/	/	/
HS-S60-101-72	R22 R404A R134a R407C	3-1/8" (80mm)	psi/bar	°C	72" 600~3000psi	/	/	/
HS-S60-102	R32 R410A	3-1/8" (80mm)	psi/bar	°C	60" 800~4000psi	/	/	/
HS-S60-103	R410A R22 R407C R134a	3-1/8" (80mm)	psi/bar	°C	60" 800~4000psi	/	/	/
HS-S60-104	R410A R404A R407C R134a	3-1/8" (80mm)	psi/bar	°C	60" 800~4000psi	/	/	/
HS-S60-101-A	R22 R404A R134a R407C	3-1/8" (80mm)	Psi/bar	°C	60" 600~3000psi	/	1pc	/
HS-S60-102-A	R410A R32	3-1/8" (80mm)	Psi/bar	°C	60" 800~4000psi	/	1pc	/
HS-S60-105-A-60	R404A R407C R22 R134a	3-1/8" (80mm)	psi/bar	°C	60" 600~3000psi	1. HS-MH 2. HS-ML	1 pc	取芯工具1只 Core remover *1
HS-S60-105-A-72	R404A R407C R22 R134a	3-1/8" (80mm)	psi/bar	°C	72" 600~3000psi	1. HS-MH 2. HS-ML	1 pc	取芯工具1只 Core remover *1
HS-S60-106A	R410A R22 R134a R404A	3-1/8" (80mm)	psi/bar	°C	60" 800~4000psi	/	/	R410A转接头2只 R410A adapter *2

表组系列 MANIFOLD GAUGE SET

HS-236



产品特点 Product Characteristics

阀体 Valve body

- 紧凑的阀体设计,便携易携
Compact valve body design, convenient and easy to carry

手轮 Knob

- 符合人体功能学的铝制手轮,舒适耐用
Gentle and comfortable aluminium knob

视液镜 Liquid indicator

- 防爆视液镜 Explosion-proof liquid indicator



工具套件
高档皮箱包装
方便收纳和携带



工具套件
彩盒
经济实用

选型 Model selection



HS-S36G

HS-404G

HS-236A

HS-260A-OA

选型表 Model selection


型号 Model	压力表 Pressure gauge				加液管 Refrigerant charging hose	额外配置 Accessories		
	制冷剂 Refrigerant	表盘大小 Diameter	压力单位 Pres.unit	温度单位 Temp.unit		快速接头 Quick coupler	其他 Other	包装 Package
HS-S36G	R134a R404A R22 R407C	80mm(3-1/8")	psi/MPa	°C	36" 600-3000psi	HS-12B	取芯工具1只 Core remover *1	彩盒 Paper box
HS-404G	R134a R404A R22 R407C	80mm(3-1/8")	psi/MPa	°C	36" 600-3000psi	HS-12B	开瓶器1只 Can tap valve *1	彩盒 Paper box

选型表 Model selection

型号 Model	压力表 Pressure gauge				加液管 Refrigerant charging hose	额外配置 Accessories		
	制冷剂 Refrigerant	表盘大小 Diameter	压力单位 Pres.unit	温度单位 Temp.unit		快速接头 Quick coupler	其他 Other	包装 Package
HS-236A-60	R22 R134a R404A R407C	70mm(2-1/2")	psi kg/cm2	°C	60" 600-3000psi	1. HS-MH 2. HS-ML	/	皮箱 Plastic case
HS-236A-72	R22 R134a R404A R407C	70mm(2-1/2")	psi/bar	°C	72" 600-3000psi	1. HS-MH 2. HS-ML	/	皮箱 Plastic case
HS-236-36	R22 R134a R404A R407C	70mm(2-1/2")	psi/bar	°C	36" 600-3000psi	/	/	彩盒 Paper box
HS-236-60	R22 R134a R404A R407C	70mm(2-1/2")	psi/bar	°C	60" 600-3000psi	/	/	彩盒 Paper box
HS-236-72	R22 R134a R404A R407C	70mm(2-1/2")	psi/bar	°C	72" 600-3000psi	/	/	彩盒 Paper box
HS-260A-OA	R410A R22 R134a R404A	70mm(2-1/2")	psi/bar	°C	60" 600-3000psi	1. HS-MH 2. HS-ML	/	皮箱 Plastic case

表组系列 MANIFOLD GAUGE SET

HS-536C



产品特点 Product Characteristics

阀体 Valve body

- 一体式铜阀结构, 性能可靠
Integrated copper valve structure, reliable performance

手轮 Knob

- 符合人体功能学的铝制手轮, 舒适耐用
Gentle and comfortable aluminium knob

工具套件 Tool kit
彩盒 Paper box
经济实用 economical and practical



选型 Model selection



HS-536A	HS-536C	HS-536G-R410A
---------	---------	---------------

选型表 Model selection

型号 Model	压力表 Pressure gauge				加液管 Refrigerant charging hose	额外配置 Accessories		
	制冷剂 Refrigerant	表盘大小 Diameter	压力单位 Pres.unit	温度单位 Temp.unit		快速接头 Quick coupler	其他 Other	包装 Package
HS-536A	R410A R22 R134a R404A	70mm(2-1/2")	psi/bar	°C	36" 600~3000psi	/	/	彩盒 Paper box
HS-536C	R22 R404A R407C R134a	70mm(2-1/2")	psi/bar	°C	36" 600~3000psi	/	/	彩盒 Paper box
HS-536G-R410A	R22 R134a R404A R410A	70mm(2-1/2")	psi/bar	°C	36" 800~4000psi	/	/	彩盒 Paper box

表组系列 MANIFOLD GAUGE SET

HS-473AH/HS-473AL

工具套件 Tool kit
彩盒 Paper box
经济实用 economical and practical



产品特点 Product Characteristics

单表阀 Single manifold gauge

- 单表设计, 经济实用
- Single meter design, economical and practical

阀体 Valve body

- 一体式铜阀结构, 性能可靠
- Integrated copper valve structure, reliable performance

视液镜 Liquid indicator

- 独特而实用的铜阀带视液设计
- Unique and practical designed sight glass

手轮 Knob

- 符合人体功能学的铝制手轮, 舒适耐用
- Gentle and comfortable aluminium knob



选型 Model selection



HS-473AH HS-473AL HS-466NAH HS-466NAL

选型表 Model selection

型号 Model	压力表 Pressure gauge				加液管 Refrigerant charging hose	额外配置 Accessories		
	制冷剂 Refrigerant	表盘大小 Diameter	压力单位 Pres.unit	温度单位 Temp.unit		快速接头 Quick coupler	其他 Other	包装 Package
HS-473AH-36	R410A R22 R134a R407C	80mm(3-1/8")	psi/bar	°C	36" R/Y 800~4000psi	/	R410A转换接头 *1 R410A adapter *1	彩盒 Paper box
HS-473AH-60	R410A R22 R134a R407C	80mm(3-1/8")	psi/bar	°C	60" R/Y 800~4000psi	/	R410A转换接头 *1 R410A adapter *1	彩盒 Paper box
HS-473AH-72	R410A R22 R134a R407C	80mm(3-1/8")	psi/bar	°C	72" R/Y 800~4000psi	/	R410A转换接头 *1 R410A adapter *1	彩盒 Paper box
HS-473AL-36	R410A R22 R134a R407C	80mm(3-1/8")	psi/bar	°C	36" B/Y 800~4000psi	/	R410A转换接头 *1 R410A adapter *1	彩盒 Paper box
HS-473AL-60	R410A R22 R134a R407C	80mm(3-1/8")	psi/bar	°C	60" B/Y 800~4000psi	/	R410A转换接头 *1 R410A adapter *1	彩盒 Paper box
HS-473AL-72	R410A R22 R134a R407C	80mm(3-1/8")	psi/bar	°C	72" B/Y 800~4000psi	/	R410A转换接头 *1 R410A adapter *1	彩盒 Paper box
HS-466NAH	R410A R22 R404A R134a	70mm(2-1/2")	psi/bar	°C	/	/	/	彩盒 Paper box
HS-466NAL	R410A R22 R404A R134a	70mm(2-1/2")	psi/bar	°C	/	/	/	彩盒 Paper box

铜配件系列 BRASS FITTINGS

铜封环 Copper sealing ring

- 优质铜合金
- 接口齐全

- High quality copper alloy
- Complete connectors



铜封环 Copper sealing ring

1/4 3/8 1/2 5/8 3/4

铜封帽 Copper cap

- 优质铜合金
- 接口齐全

- High quality copper alloy
- Complete connectors



铜封帽 Copper cap

1/4 3/8 1/2 5/8 3/4

毛细管带钠子 Capillary tube with nut

- 优质铜合金
- 焊接结构, 牢固可靠
- 接口, 长度可接受定制

- High quality copper alloy
- Welding structure, firm and reliable
- Connector and length can be customized



毛细管带钠子 Capillary tube with nut	长度 Length	接口 Connector
HS-1350	1M	1/4 SAE
HS-1351	1.5M	1/4 SAE
HS-1352	2M	1/4 SAE

冷媒瓶 CYLINDER


产品特点 Product Characteristics

Cylinder valve

- 一体式铜阀结构, 安全可靠
- 改性PTFE密封垫, 性能优越
- 安全泄压, 2.8MPa-5.5MPa可调节
- 两个接口为高压(液态), 低压(气态)
- 铜管长度可接受定制

- Integrated brass valve structure, safe and reliable
- Modified PTFE gasket, superior performance
- Safe pressure relief, adjustable from 2.8MPa-5.5MPa
- Two connectors: high pressure (liquid) and low pressure (vapor)
- The length of brass pipe can be customized

选型 Model selection



Cylinder valve



Cylinder 12L / 30L

铜配件系列 BRASS FITTINGS

铜子 Nut

- 优质铜合金锻制而成
- 接口齐全
- Forged from high-quality copper alloy
- Complete connectors



1/4 3/8 1/2 5/8 3/4

铜子 Nut

1/4 3/8 1/2 5/8 3/4

双接头 Union connector

- 优质铜合金
- 接口齐全
- High quality copper alloy
- Complete connectors



1/4 3/8 1/2 5/8 3/4

双接头 Union connector

1/4 3/8 1/2 5/8 3/4

转换接头 Adapter

- 优质铜合金 • High quality copper alloy
- 卡簧结构, 环保 • Circlip structure, environmental protection

转换接头 Adapter	接口A Connector A	接口B Connector B
R22转换接头 R22 Adapter	1/4 SAE(内) 1/4 SAE(female)	5/16 SAE(外) 5/16 SAE(male)
R410A转换接头 R410 Adapter	5/16 SAE(内) 5/16 SAE(female)	1/4 SAE(外) 1/4 SAE(male)



选型表 Model selection

型号 Model	接口A Connector A	接口B Connector B	适用工质 Refrigerants
铜瓶阀 Cylinder valve	PZ27.8	1/4SAE	R22/R134a/R404A/R407C/R410A

型号 Model	尺寸 Size
冷媒瓶 12L Cylinder 12L	1/4 SAE
冷媒瓶 30L Cylinder 30L	1/4 SAE

快速接头 QUICK COUPLER SERIES

HS-QL-1/4 / HS-QH-1/4



No man understands a deep book until he has seen and lived at least part of its contents.

— Chow Yun-fat, Actor

技术参数 Technical Parameters

适用工质 HS/R410A adapter:R134a

接口 HS/black charging hose:1/4SAE

产品特点 Product Characteristics

- 符合SAE J639标准
 - 开度可调, 精准加注
 - 精致小巧, 外形精美
 - 结构独特, 创新产品
- Meet SAE J639 standard
 - Adjustable opening, precise filling
 - Exquisite and compact, beautiful appearance
 - Unique structure, innovative products

把手握紧, 里面什么都没有, 但把手张开, 就可以拥有一切。

— 周润发 (演员)

快速接头 QUICK COUPLER SERIES

HS-ML-1/4 / HS-MH-1/4

产品特点 Product Characteristics

行业标准 Standard

- 符合J639标准
Meet the J639 standard

精准操作 Precise operation

- 开度可调,精准加注
Adjustable opening, precise filling



HS-MH-14x1.5

HS-ML-14x1.5

HS-MH-1/4

HS-ML-1/4

快速接头 QUICK COUPLER SERIES

HS-MH-BMW/HS-12A/HS-12B

产品特点 Product Characteristics

HS-MH-BMW

行业标准 Standard

- 符合J639标准
Meet the J639 standard

精准操作 Precise operation

- 开度可调,精准加注
Adjustable opening, precise filling
- 专为BMW特殊车型设计
Specially designed for BMW

HS-12A/HS-12B

经济实用

economical and practical

选型 Model selection



HS-MH-BMW

HS-12A

HS-12B

选型表 Model selection

型号 Model	适用制冷剂 Refrigerants	附件 Accessories	类型 Type	备注 Remark
HS-MH-14x1.5	R134a	adapter M14x1.5-1/4 SAE	手动型 Manual type	高压 high side
HS-ML-14x1.5		adapter M14x1.5-1/4 SAE	手动型 Manual type	低压 low side
HS-MH-1/4		—	手动型 Manual type	高压 high side
HS-ML-1/4		—	手动型 Manual type	低压 low side

快速接头 QUICK COUPLER SERIES

HS-MH-R744/HS-ML-R744



- 符合J639标准
- 自锁结构,环保可靠
- 开度可调,精准加注
- 一体式阀体结构,超高耐压,爆破压力≥8700Psi (60MPa)
- 自备泄压,装卸方便

- Meet the J639 standard
- Self-locking structure, environmental protection and reliable
- Adjustable opening, precise filling
- One-piece valve body structure, ultra-high pressure resistance, burst pressure ≥8700Psi (60MPa)

选型表 Model selection

型号 Model	制冷剂 Refrigerant	接口 Connection	类型 Type	备注 Remark
HS-MH-R744	R744(CO ₂)	1/4SAE	手动型 Manual type	高压high side
HS-ML-R744		1/4SAE	手动型 Manual type	低压low side

产品特点 Product Characteristics

行业标准 Standard

- 符合J639标准
- Meet the J639 standard

安全可靠 Reliability

- 自锁结构,环保可靠
- Self-locking structure, environmental protection and reliable

精准操作 Precise operation

- 开度可调,精准加注
- Adjustable opening, precise filling



选型 Model selection



HS-MH-1234	HS-ML-1234	HS-MH-S	HS-ML-S
------------	------------	---------	---------

选型表 Model selection

型号 Model	适用制冷剂 Refrigerants	类型 Type	备注 Remark
HS-MH-1234	R1234yf	手动型 Manual type	高压 high side
HS-ML-1234		手动型 Manual type	低压 low side

选型表 Model selection

型号 Model	适用制冷剂 Refrigerants	附件 Accessories	类型 Type	备注 Remark
HS-MH-S	R134a	转换接头 adapter(M14x1.5-1/4 SAE)	手动型 Manual type	高压 high side
HS-ML-S		转换接头 adapter(M14x1.5-1/4 SAE)	手动型 Manual type	低压 low side
HS-MH-S 1/4 SAE		—	手动型 Manual type	高压 high side
HS-MH-L 1/4 SAE		—	手动型 Manual type	低压 low side

CHARGING VALVE SERIES

加注阀系列



产品特点 Product Characteristics


手轮Knob

- 符合人体功能学的铝制手轮，舒适耐用
Gentle and comfortable aluminium knob

防回流设计non-return design

- 防止制冷剂倒流，防爆
prevent refrigerant backflow,burst proof

开瓶器A系列 CAN TAP VALVE 防爆设计



选型 Model selection



A B



A B



A B

HS-338A

HS-339A

HS-340A

选型表 Model selection

型号 Model	适用制冷剂 Refrigerants	接口A Connector A	接口B Connector B	类型 Type
HS-338A	R22	M12×1.25	1/4 SAE	顶针型 pin type
HS-339A	R134a	M14×1.25	1/4 SAE	顶针型 pin type
HS-340A	通用 universal refrigerants	通用 general type	1/4 SAE	顶针型 pin type

开瓶器系列 CAN TAP VALVE

产品特点 Product Characteristics

经济实用

economical and practical



HS-338/HS-339



HS-341



HS-340

空调加液阀
Refrigerant Charging Control Valve

产品特点 Product Characteristics

手轮 Knob

- 铝制手轮, 舒适耐用
- Aluminum knob, comfortable and durable
- 安全可靠, 节能环保
- Safe and reliable, energy saving and environmental protection



选型 Model selection



HS-1221



HS-1222



HS-1223

选型表 Model selection

型号 Model	适用制冷剂 Refrigerants	接口A Connector A	接口B Connector B	类型 Type
HS-338	R22	M12×1.25	1/4 SAE	顶针型 pin type
HS-339	R134a	M14×1.25	1/4 SAE	顶针型 pin type
HS-341	R22 R134a R410A	7/16-28UNF	1/4 SAE	顶杆型 stem type
HS-340	通用 universal refrigerants	通用 general type	1/4 SAE	顶针型 pin type

选型表 Model selection

型号 Model	适用制冷剂 Refrigerants	接口A Connector A	接口B Connector B	类型 Type
HS-1221	R410A R32	5/16 SAE(内)(female)	1/4 SAE	顶杆型 stem type
HS-1222	R22 R404A R407C	1/4 SAE(内)(female)	1/4 SAE	顶杆型 stem type
HS-1223	R410A R32	5/16 SAE(内)(female)	5/16 SAE	顶杆型 stem type

备注:1/2ACME, 1/2ACME反牙, 5/16SAE反牙等特殊螺纹皆可接受定制
Remarks: Special threads such as 1/2ACME, 1/2ACME left-handed, 5/16SAE left-handed, etc. can be customized

三色管 REFRIGERANT CHARGING HOSE SERIES

产品特点 Product Characteristics



SAE J2196
SAE J2888 R1234yf

行业标准 Standard

- 三色管符合SAE J2196 SAE J2888标准
Meet the SAE J2196 and SAE J2888 standard

安全可靠 Reliability

- 改性PTFE密封材质,适用多种制冷剂,使用寿命更长
Modified PTFE sealing material, suitable for a variety of refrigerants, longer service life

密封性强 Sealing

- 带六角的滚花,可使用扳手锁紧,保证密封效果
Knurled with hexagon, can be locked with a wrench to ensure the sealing effect
- 8角液压,受力均匀,加强密封
8 angle hydraulic pressure, uniform force, strengthened sealing


实用方便 Convenience

- 接口,长度均可定制
Connector and length can be customized


选型 Model selection



Charging hose



Charging hose with ball valve



Charging hose with ball valve

选型表 Model selection


型号 Model	适用制冷剂 Refrigerants	工作压力 Working Pressure	爆破压力 Burst Pressure	长度 Length	接口 Connector
HS-336	R22 R134a R404A R407c	600psi	3000psi	36"	红Red: 1/4SAE-1/4SAE 蓝Blue: 1/4SAE-1/4SAE 黄Yellow: 1/4SAE-1/4SAE
HS-360				60"	
HS-372				72"	
HS-336-R410A	R22 R134a R404A R407c R410A	800psi	4000psi	36"	红Red: 1/4SAE-5/16SAE 蓝Blue: 1/4SAE-5/16SAE 黄Yellow: 1/4SAE-1/4SAE
HS-360-R410A				60"	
HS-372-R410A				72"	
HS-336-BV	R22 R134a R404A R407c R410A	800psi	4000psi	36"	红Red: 1/4SAE-1/4SAE 蓝Blue: 1/4SAE-1/4SAE 黄Yellow: 1/4SAE-1/4SAE
HS-360-BV				60"	
HS-372-BV				72"	
HS-115-1/4	R22 R134a R404A R407c R410A	800psi	4000psi	6"	1/4SAE-1/4SAE
HS-115-5/16				6"	1/4SAE-5/16SAE

小球阀 BALL SHUT OFF VALVE

产品特点 Product Characteristics

- 一体式结构,性能稳定
- 双重密封,安全可靠
- 改性PTFE密封材质,适用多种制冷剂
- Integrated copper valve structure, stable performance
- Double sealing, safe and reliable
- Modified PTFE sealing material, suitable for a variety of refrigerants

选型 Model selection




选型表 Model selection				
型号 Model	分组 Group	适用制冷剂 Refrigerants	接口A Connector A	接口B Connector B
1320-01	R22 R134a R502 R404A R407C R410A	1/4 SAE M	1/8 NPT F	
1320-05			1/4 SAE M	1/4 SAE M
1320-06		5/16 SAE M	1/4 SAE M	
1320-11		5/16 SAE M	1/4 SAE F 90°	
1320-07		1/4 SAE M	1/4 SAE F 90°	
1320-09		1/4 SAE M	5/16 SAE F 90°	
1320-14		5/16 SAE M	5/16 SAE F 90°	

备注:1/2ACME,1/2ACME反牙,5/16SAE反牙等特殊螺纹皆可接受定制
Remarks: Special threads such as 1/2ACME, 1/2ACME left-handed, 5/16SAE left-handed, etc. can be customized

SCHRADER VALVE REMOVER

气门芯装卸工具



选型表 Model selection				
型号 Model	分组 Group	适用制冷剂 Refrigerants	接口A Connector A	接口B Connector B
1320-08	R22 R134a R502 R404A R407C R410A	1/4 SAE M	1/4 SAE M 90°	
1320-13			5/16 SAE M	5/16 SAE M 90°
1320-02		1/4 SAE M	1/4 SAE F	
1320-03		1/4 SAE M	5/16 SAE F	
1320-04		1/4 SAE M	3/8 SAE F	
1320-10		5/16 SAE M	1/4 SAE F	
1320-12		5/16 SAE M	5/16 SAE F	

气门芯装卸工具 SCHRADER VALVE REMOVER

产品特点 Product Characteristics

HS-1430 / HS-1424

- 接口可灵活转换
- 工作中可装卸阀芯
- The connector can be flexibly converted
- Assemble and disassemble valve core under running condition of refrigeration system

HS-1431

- 可双头使用
- 简便实用
- Both ends can be used
- Simple and practical

选型 Model selection



HS-1430



HS-1431

注油器 OIL INJECTOR

产品特点 Product Characteristics

HS-1416 / HS-1417

- 1/4ACME, 1/2ACME反牙, 5/16SAE反牙等特殊螺纹皆可接受定制
- 单向充注, 有效防回流
- 为系统充注荧光试剂和冷冻油
- Special threads such as 1/4ACME, 1/2ACME left-handed, 5/16SAE left-handed, etc. can be customized
- One-way filling, effectively preventing backflow
- Filling the fluorescent reagents and refrigerant oil for system



HS-1416



HS-1417

选型表 Model selection

型号 Model	接口 Connector	适用工况 Working Condition
HS-1430	1/4 SAE & 5/16 SAE	5V1
HS-1431	通用 General	5V1 & 6V1

选型表 Model selection


型号 Model	接口 Connector	容积 Capacity
HS-1416	1/4 SAE	70ml
HS-1417	1/4 SAE	14ml

荧光加液器 FLUORESCENT LIQUID FILLER

产品特点 Product Characteristics

- 1/2ACME, 1/2ACME反牙, 5/16SAE反牙等特殊螺纹皆可接受定制
- 为系统充注荧光试剂和冷冻油

- Special threads such as 1/2ACME, 1/2ACME left-handed, 5/16SAE left-handed, etc. can be customized
- Filling the fluorescent reagents and refrigerant oil for system



清洗瓶 A/C FLUSH CLEANER

产品特点 Product Characteristics

- 软管连接, 使用轻便灵活
- 深度清洗冷凝器和蒸发器
- 超压自动排泄, 安全可靠

- Flexible hose connection, easy to use
- Can clean the condenser and evaporator deeply
- Automatic discharge of overpressure, safe and reliable



选型表 Model selection

型号 Model	接口A Connector A	接口B Connector B	容积 Capacity
HS-1418	1/4 SAE	1/4 SAE	60ml

选型表 Model selection

型号 Model	接口 Connector	工作压力 Working Pressure	容积 Capacity
HS-1415R	1/4 SAE	1Mpa	1000ml

割刀 CUTTER

产品特点 Product Characteristics

- 精密螺杆机械结构：灵活进给
- 多滚轮结构：作业时刀片保持在同一圈内切割
- 凹槽滚轮结构：可贴近管子扩口切割
- GCr15刀片：准确锋利切断管件
- Precision screw mechanical structure: smart moving
- Multi -rolling wheel structure: same circle cutting will be kept during operation
- The groove wheel structure: can be close to the tube expansion cutting
- GCR15 blade: precise and sharp cutting

选型 Model selection



HS-TD19	HS-TD32	HS-TD50	HS-TD70
---------	---------	---------	---------

选型表 Model selection	
型号 Model	尺寸 Size
HS-TD19	Φ3-Φ19
HS-TD32	Φ4-Φ32
HS-TD50	Φ5-Φ50
HS-TD70	Φ6-Φ70

回收机 RECOVERY MACHINE

产品特点 Product Characteristics

- 无油压缩机，可回收大部分常用冷媒
- 自净化功能，清除机内残留冷媒
- 低压保护，自动停机
- 高压保护，复位按钮
- Oil -free compressor, suitable for all commonly used refrigerants
- Self -purification function, can remove the residual refrigerants in the machine
- Low -pressure protection, automatic shutdown
- High pressure protection, reset button

选型 Model selection



选型表 Model selection									
型号 Model	适用制冷剂 Refrigerants	电源 Power Supply	电机 Power Supply	压缩机 Compressor	高压保护 High Pressure Shut-Off	工作温度 Operating Temperature	回收速率 Recovery Rate	外形尺寸 Dimensions (mm)	
R250/R250F	• R12, R134a, R401C, R406A, R500 • R407D, R408A, R409A, R411A, R411B, R412A, R502, R509, R22, R401A, R401B, R402B, R407C • R402A, R404A, R407A, R407B, R410A, R507	220-240VAC/ 50-60Hz 110-120VAC/ 60Hz	3/4	Oil-free Piston style Air cooled	38.5bar/ 3850kPa	0°C~40°C/ 32°F~104°F	气态Vapor:0.26kg/min 液态Liquid:1.85kg/min 推拉模式 Push/Pull:6.22kg/min	418×250×345	
R500/R500F			1	Oil-free Piston style Air cooled	38.5bar/ 3850kPa	0°C~40°C/ 32°F~104°F	气态Vapor:0.52kg/min 液态Liquid:3.70kg/min 推拉模式 Push/Pull:9.95kg/min	418×250×345	