

# TECHNICAL DATA SHEET FOR PVC BELTING

BELT TYPE:7.0MM GREEN MARBLE BELT

FABRIC TOP DIAMOND

CODE: 3/70 D/P PG

CONSTRUCTION	
Top Cover	Material: PVC Cover structure:DIAMOND Color: PETROL GREEN
Intermed. layer	Material: PVC Color:PETROL GREEN
Bottom cover	Material:FABRIC Cover structure: Color:
Upper fabric	Warp: MARBLE BELT FABRIC Weft:
Intermed. fabric	Warp: MARBLE BELT FABRIC Weft: -
Bottom fabric	Warp: MARBLE BELT FABRIC Weft: -
Top Cover Thickness:1.5mm	
Bottom Cover Thickness:	
Total Thickness: 7.0 mm	

DATA
Hardness: Top cover 80 Shore A Bottom cover 80 Shore A
Antistatic properties: Top cover - : Bottom cover -
Temperature: Min. : -10 °C : Max. : 80°C
Pulley-diameter 1. Norm flexing Min.ø: 140 2. Back flexing Min.ø: 140
No.of plies: 3 PLY
Breaking load: -
Pull for 1%
Elongation: 45 N/mm
Weight: 8.8 kg/m <sup>2</sup>
COEFFICIENT OF FRICTION
Steel:
Plastic/Wood:

Additional information:	MAX. PRODUCTION WIDTH: 2000MM
Applications:	GENERAL PURPOSE OF LIGHT DUTY CONVEYING SYSTEM
Special characteristics	
Joint methods	FINGER SPLICING OVERLAP SPLICING MECHANICAL FASTENER