

Beijing EXQUISITE International Development Co., Ltd.

TECHNICAL DATA SHEET FOR PU BELTING

BELT TYPE: 3MM PU WHITE GLOSSY

CODE: 2/30 S/P PG U

Build Convenience Of Global Conveyor Belt

| CONSTRUCTION | |
|----------------------------|---|
| Top Cover | Material: PU Cover structure: GLOSSY Color: WHITE |
| Intermed. layer | Material: PU Color: PETROL WHITE |
| Bottom cover | Material: FABRIC Cover structure: Color: |
| Upper fabric | Warp: Polyester Weft: Polyester/Monofil |
| Intermed. fabric | Warp: Weft: |
| Bottom fabric | Warp: Polyester Weft: Polyester/Carbon |
| Top Cover Thickness: 1.0mm | |
| Bottom Cover Thickness: - | |
| Total Thickness: 3.0 mm | |

| DATA |
|---|
| Hardness: Top cover 90 Shore A Bottom cover - |
| Antistatic properties: Top cover - : Bottom cover YES |
| Temperature: Min. : -10 °C : Max. : 80°C |
| Pulley-diameter 1. Norm flexing Min. \varnothing : 100 2. Back flexing Min. \varnothing : 120 |
| No. of plies: 2 PLY |
| Breaking load: 180 N/mm |
| Pull for 1% |
| Elongation: 10N/mm |
| Weight: 3.75kg/m ² |
| COEFFICIENT OF FRICTION |
| Steel: |
| Plastic/Wood: |

| | |
|-------------------------|--|
| Additional information: | MAX. PRODUCTION WIDTH: 3000MM |
| Applications: | GENERAL PURPOSE OF LIGHT DUTY CONVEYING SYSTEM |
| Special characteristics | BOTTOM IS COATED WITH TRANSPARENT PU |
| Joint methods | FINGER SPLICING OVERLAP SPLICING MECHANICAL FASTENER |



HQ: Aoyu Technology Bldg, Daxing
CBD, Beijing, China, 100162
Mobile/Whatsapp/Messenger: +86 188
111 591 71
Official Web:
<http://www.exquisiteconveyorbelt.com/>